



Stamina

100% recycled vulcanized rubber mat. This 4' x 6' mat can be adhered, loose laid, or interlocked. The non-porous surface makes it an ideal mat for use in hockey arenas, free weight areas in fitness facilities or anywhere that a tough, slip-resistant, easy to clean flooring is required.



Technical Specifications

Hardness Shore A	ASTM D2240	80
Wear Layer Thickness	ASTM F410	>.050 Passes
Static Load Resistance	ASTM F970	0.002 Passes
Resistance to Chemicals	ASTM F925	Passes
Resistance to Heat	ASTM F1514	4.29 Passes
Abrasion Resistance	ASTM D3389	0.16 gr. Passes
Dimensional Stability	ASTM F2199	Across Passes
Critical Radiant Flux	ASTM E648-03	No Class
Co-efficient of Friction	ASTM C1028	>.80 dry >.64 wet
Moisture Absorption	ASTM D570	0.27%
Thickness	ASTM F386	Passes
Size	ASTM F2055	Passes
Squareness	ASTM F2055	Passes
Quality of Cut	ASTM F511	Passes
Contributes to LEED Points		Yes

Size Specifications

Construction				100% recycled vulcanized rubber		
Thickness	Square			Interlock		
	Dimension	Weight	Area	Dimension	Weight	Area
10 mm (3/8")	4' x 6' (1.2m x 1.8m)	60 lbs.	24 sq. ft.	44.3" x 66.5'	56 lbs.	20.46 sq. ft.
				22.2" x 22/2	9 lbs.	3.42 sq. ft.
12 mm (1/2")	4' x 6' (1.2m x 1.8m)	70 lbs.	24 sq. ft.	44.3" x 66.5"	66 lbs.	20.46 sq. ft.
*17 mm (3/4")		100 lbs.		44.3' x 66.5"	86 lbs.	20.46 sq. ft.

* black only

Standard Colors



Ask us about creating a unique statement or how to reinforce your corporate identity by custom cutting a logo for you.

Colors:

100 Black **110** Black with 20% Red speckle **120** Black with 20% Grey speckle **130** Black with 20% Blue speckle

190 Black with 20% Earth speckle

Custom colors are available by special order

Finishes: Smooth top, textured bottom