

Cleaning and Maintenance

Choosing the right equipment for the right size job is important. Large auto scrubbers may be useful for wide-open areas, such as large aerobic studios. Rotary machines or deck brushes may be most suitable to easily maneuver around fitness equipment in strength and cardio areas.

Initial Cleaning After Installation

- Wait 24 to 48 hours after installation before proceeding with floor maintenance.
- Sweep matting to remove all loose dirt and debris.
- Do only small areas of floor at a time
- Using a damp mop (not soaking wet) apply a light PH neutral detergent diluted with water. A product that may be used is listed below.

(TASKI PROFI - A highly effective non-ionic oil and grease remover for resilient rubber flooring. The neutral pH and bio-degradability make it an ideal product for rapid emulsification of oil and grease.)

- Scrub the damp floor using a rotary buffing machine equipped with a medium 'Scotch Brite' pad, and immediately extract damp residue with wet/dry vacuum
- Rinse with clean water and mop and repeat extraction/drying method.
- Stay off floor until area is dry.

(TASKI WIWAX - A unique blend of detergents, waxes, and polymers formulated to clean and maintain rubber flooring, and provide a light polymer and wax film for additional protection.)

Regular Maintenance

SportFLOOR Décor may be cleaned at any time using a damp mop with a PH neutral cleaner diluted with water. Ensure that any moisture is immediately extracted after cleaning.

Precautions:

SportFLOOR Décor must not be cleaned with any petroleum based cleaners. If any petroleum fuels are spilled on the matting, it should be removed immediately to avoid damage to the matting and voiding of warranty.